

Datum: 20.06.2026



(slika je simbolična)

krogelni ventil s prirobnico, Pneumat. vklop, DN 80

Kategorija: [Stainless steel ball valves compact flange type](#)Šifra: **103645RIE**

Kratek opis

Compact flange ball valve, Pneumat. actuation drive, double-acting, Stainless steel, Operating temp. -10°C to 200°C, PN max 16 bar
2-way ball valves compact flange type, full bore.
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Tehnične Specifikacije

| | |
|-----------------------------|---|
| Delovna temperatura | -10 °C to 200 °C (depending on the operating pressure) |
| Adapter ventila | Acc. to NAMUR |
| Material krogelnega ventila | Stainless steel 1.4408, with ISO flange |
| Pogonski material | Anodised aluminium |
| Premaz za krogelni ventil | PTFE |
| Premaz za pogon | NBR |
| Različica | double-acting |
| Max. vodeni tlak [bar] | 5.5 |
| PN [bar] | 16 |
| DN | 80 |
| Kot vrtenja [°] | 90 |
| F [mm] | 110.5 |
| C [mm] | 120.0 |
| E [mm] | 138.0 |
| D [mm] | 200.0 |
| A [mm] | 209.0 |
| B [mm] | 240.0 |