

Datum: 10.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

[krogelni ventil stinardna oblika, polni pretok, IT/ET, G 3/4](#)

Kategorija: [Ball valve, standard type, IT/ET](#)
Šifra: **103136RIE**

Kratek opis

Ball valve standard design, full passage, IT/ET, nickel-plated brass, Operating temp. -15°C to 90°C, G 3/4, DN 20, PN max. 40 bar

Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material	Nickel-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G 3/4
Ročica	Aluminium, painted black
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE
E [mm]	10.5
F [mm]	10.5
DN	20
PN [bar]	40
B [mm]	53.4
L [mm]	69.5
Max. delovna temperatura [°C]	90
A [mm]	105.0