



(slika je simbolična)

## [krogelni ventil stinardna oblika polni pretok, IT/IT, G 1 1/2](#)

Kategorija: [Ball valve, standard type, IT/IT](#)  
Šifra: **103129RIE**

### Kratek opis

Ball valve standard type, full passage, IT/IT, nickel-plated brass, Operating temp. -15°C to 90°C, G 1 1/2, DN 40, PN max. 40 bar  
Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

### Tehnične Specifikacije

|                               |   |
|-------------------------------|---|
| Min. delovna temperatura [°C] | -15   |
| Krogelno tesnilo              | PTFE  |
| Krogla                        | Chrome-plated brass   |
| Material                      | Nickel-plated brass   |
| Material navojev              | Brass with a bare metal surface                             |
| Navoj                         | G 1 1/2   |
| Ročica                        | Aluminium, painted black                                    |
| Standardni navoj              | G thread acc. to DIN EN ISO 228-1                           |
| Stebelno tesnilo              | 2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE |
| E [mm]                        | 14.5  |
| F [mm]                        | 14.5  |
| DN                            | 40  |
| PN [bar]                      | 40  |
| B [mm]                        | 76.1  |
| Max. delovna temperatura [°C] | 90  |
| L [mm]                        | 91.5  |
| A [mm]                        | 130.0   |