

Datum: 12.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## [krogelni ventil stinardna oblika, polni pretok, IT/IT, G 3](#)

Kategorija: [Ball valve, standard type, IT/IT](#)  
Šifra: **103132RIE**

### Kratek opis

Ball valve standard type, full passage, IT/IT, nickel-plated brass, Operating temp. -15 °C to 90 °C, G 3, DN 80, PN max. 40 bar  
Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material	Nickel-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G 3
Ročica	Aluminium, painted black
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE
E [mm]	18.5
F [mm]	18.5
PN [bar]	40
DN	80
Max. delovna temperatura [°C]	90
B [mm]	127.0
L [mm]	156.0
A [mm]	260.0