



(slika je simbolična)

[krogelni ventil »ventil linija«, modra ročica, IT/IT, G 2](#)

Kategorija: [Ball valve with blue hand lever, IT/IT](#)
Šifra: **115718RIE**

Kratek opis

Ball valve »valve line« Hand lever blue, Nickel-plated brass, IT/IT, G 2, DN 50, Operating temp. -20 °C to 120 °C, PN max 25 bar
Extremely economical standard ball valves made of nickel-plated brass for compressed air, water, non-toxic and non-corrosive gases and liquids.

Tehnične Specifikacije

| | |
|-------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Krogelno tesnilo | PTFE |
| Krogla | Nickel-plated brass |
| Material navojev | Nickel-plated brass |
| Navoj | G 2 |
| Ohišje | Nickel-plated brass |
| Ročica | Steel Q235-A (1.0038) with PVC-coating |
| Standardni navoj | G thread acc. to DIN EN ISO 288-1 |
| Stebelno tesnilo | NBR |
| Max. obratovalni tlak [bar] | 25 |
| C Ø [mm] | 45.0 |
| DN | 50 |
| B [mm] | 79.0 |
| L [mm] | 99.0 |
| Max. delovna temperatura [°C] | 120 |
| A [mm] | 160.0 |