

Datum: 04.06.2026



(slika je simbolična)

krogelni ventil, visoki tlak, G notranji navoj, jeklo, G 1

Kategorija: [High-pressure ball valve, steel, G female thread](#)
Šifra: **103520RIE**

Kratek opis

Ball valve, High pressure design, G interior thread, Steel,
Operating temperature -10 °C to 100 °C, G 1, DN 25, PN
max. 420 bar

For liquid and lubricating media.

Available versions:

- For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1.
- For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1.
- With female pipe thread acc. to DIN ISO 228-1 (BSP).

Tehnične Specifikacije

| | |
|-------------------------------|--------------------------|
| Min. delovna temperatura [°C] | -10 |
| Bore inball | Full bore |
| Gred izbirnika | Steel |
| Kontrolno kroglično tesnilo | POM |
| Krogla | Hard-chrome plated steel |
| Navoj | G 1 |
| Ohišje | Steel |
| Tesnilo gredi izbirnika | NBR |
| DN | 25 |
| Max. delovna temperatura [°C] | 100 |
| L [mm] | 115.0 |
| B [mm] | 128.0 |
| A [mm] | 187.0 |
| Max. obratovalni tlak [bar] | 420 |