

Datum: 23.04.2026



(slika je simbolična)

## [krogelni ventil, visoki tlak, G notranji navoj, jeklo, G 3/4](#)

Kategorija: [High-pressure ball valve, steel, G female thread](#)  
Šifra: **103519RIE**

### Kratek opis

Ball valve, High pressure design, G interior thread, Steel, Operating temperature -10 °C to 100 °C, G 3/4, DN 20, PN max. 420 bar

For liquid and lubricating media.

Available versions:

- For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1.
- For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1.
- With female pipe thread acc. to DIN ISO 228-1 (BSP).

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Bore inball	Full bore
Gred izbirnika	Steel
Kontrolno kroglično tesnilo	POM
Krogla	Hard-chrome plated steel
Navoj	G 3/4
Ohišje	Steel
Tesnilo gredi izbirnika	NBR
DN	20
L [mm]	93.0
Max. delovna temperatura [°C]	100
B [mm]	121.0
A [mm]	187.0
Max. obratovalni tlak [bar]	420