

Datum: 21.09.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

[krogelni ventil, visoki tlak, G notranji navoj, jeklo, G 3/8](#)

Kategorija: [High-pressure ball valve, steel, G female thread](#)
Šifra: **103516RIE**

Kratek opis

Ball valve, High pressure design, G interior thread, Steel, Operating temperature -10 °C to 100 °C, G 3/8, DN 10, PN max. 500 bar

For liquid and lubricating media.

Available versions:

- For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1.
- For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1.
- With female pipe thread acc. to DIN ISO 228-1 (BSP).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Bore inball	Full bore
Gred izbirnika	Steel
Kontrolno kroglično tesnilo	POM
Krogla	Hard-chrome plated steel
Navoj	G 3/8
Ohišje	Steel
Tesnilo gredi izbirnika	NBR
DN	10
B [mm]	68.0
L [mm]	73.0
A [mm]	100.0
Max. delovna temperatura [°C]	100
Max. obratovalni tlak [bar]	500