

Datum: 10.05.2026



(slika je simbolična)

[krogelni ventil visoki tlak, lahka izvedba, M30x2](#)

Kategorija: [High-pressure ball valve steel, lightweight series](#)
Šifra: **103504RIE**

Kratek opis

Ball valve, High pressure design, Lightweight series, Steel,
Operating temp. -10 °C to 100 °C, M30x2, DN 20, PN max.
420 bar

For liquid and lubricating media.

Available versions:

- For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1.
- For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1.
- With female pipe thread acc. to DIN ISO 228-1 (BSP).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Bore inball	Full bore
Gred izbirnika	Steel
Kontrolno kroglično tesnilo	POM
Krogla	Hard-chrome plated steel
Navoj	M30x2
Ohišje	Steel
Tesnilo gredi izbirnika	NBR
DN	20
O.D. za cevi [mm]	22L
L [mm]	99.0
Max. delovna temperatura [°C]	100
B [mm]	121.0
A [mm]	187.0
Max. obratovalni tlak [bar]	420