



(slika je simbolična)

## [krogelni ventil z vgrajenim izpustom, nikljana medenina, G 1 1/4](#)

Kategorija: [Ball valves with integrated strainer](#)  
Šifra: **133557RIE**

### Kratek opis

Ball valve, integrated strainer, nickel-plated brass,  
Operating temp. -20°C to 100°C, G 1 1/4, DN 28, PN max 20 bar, Mesh size 0.5  
Space and cost saving combination made of ball valve and dirt strainer in one.  
Replaces the sequence of ball valve - dirt strainer - ball valve and thus reduces installation time and costs.  
The can be removed easily in locked, pressure released status for cleaning.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass (CW617N)
Material navojev	Nickel-plated brass (CW617N)
Navoj	G 1 1/4
Ohišje	Nickel-plated brass (CW617N)
Ročica	Galvanised steel with plastic coating
Standardni navoj	G-thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	NBR / FKM
Zaslon	Stainless steel, mesh size 0.5 mm
E [mm]	17.0
PN [bar]	20
DN	28
a/f 2 [mm]	46
a/f 1 [mm]	48
D [mm]	51.5
B [mm]	74.0
L [mm]	85.0
Max. delovna temperatura [°C]	100
A [mm]	158.0