



(slika je simbolična)

[krogelni ventil z vgrajenim izpustom, nikljana medenina, G 1](#)

Kategorija: [Ball valves with integrated strainer](#)
Šifra: **133556RIE**

Kratek opis

Ball valve, integrated strainer, nickel-plated brass,
Operating temp. -20 °C to 100 °C, G 1, DN 20, PN max. 30 bar, Mesh size 0.5
Space and cost saving combination made of ball valve and dirt strainer in one.
Replaces the sequence of ball valve - dirt strainer - ball valve and thus reduces installation time and costs.
The can be removed easily in locked, pressure released status for cleaning.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass (CW617N)
Material navojev	Nickel-plated brass (CW617N)
Navoj	G 1
Ohišje	Nickel-plated brass (CW617N)
Ročica	Galvanised steel with plastic coating
Standardni navoj	G-thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	NBR / FKM
Zaslon	Stainless steel, mesh size 0.5 mm
E [mm]	15.0
DN	20
PN [bar]	30
a/f 1 [mm]	38
a/f 2 [mm]	38
D [mm]	38.7
B [mm]	50.8
L [mm]	70.1
A [mm]	100.0
Max. delovna temperatura [°C]	100