

Datum: 13.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



L-obročni del, na votli vijak G 1/8, za cev zunanja Ø 4 mm

Kategorija: [L-ring nipple](#)
Šifra: **108833RIE**

(slika je simbolična)

Kratek opis

L-ring piece, for hollow screw G 1/8, for hose exterior Ø 4 mm, Working pressure -0.98 to 16 bar, Operating temp. -20 °C to 70 °C

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Nickel-plated brass
Priporočena cev	PA, PU
Rokav	POM black
Serija	click-clock
Vpenjalni obroč	Stainless steel
Za banjo vijak	G 1/8
Za cevi O.D. [mm]	4
L2 [mm]	15.0
Max. delovni tlak [bar]	16
L1 [mm]	20.5
Max. delovna temperatura [°C]	70