



Manometer, CrNi jeklena varnostna verzija, G 1/2, 0-40 bar, Ø 100

Kategorija: [Wika](#)
Šifra: **102469RIE**

(slika je simbolična)

Kratek opis

Pressure gauge, CrNi steel, Safety design, Connection radial bottom, G 1/2, Goods class 1.0, Measurement range 0-40 bar, Ø 100

Bourdon-tube pressure gauge (safety housing), CrNi steel type, with solid baffle wall and blow-out (safety housing). Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere.

Tehnične Specifikacije

| | |
|--|------------------------|
| Min. sobna temperatura [°C] | -40 |
| Min. temperatura medija [°C] | -40 |
| Material | CrNi steel |
| Material Prozessanschluss | CrNi steel |
| Položaj povezave | radial on bottom |
| Povezava | G 1/2 |
| Prednje steklo | Laminated safety glass |
| Spodnja/Zgornja meja območja | Positive pressure |
| Razred točnosti | 1.0 |
| Stopnja rasti na območju skale - bar [bar] | 1 |
| Merilno območje max. bar | 40 |
| Max. sobna temperatura [°C] | 60 |
| Premer [mm] | 100 |
| Max. temperatura medija [°C] | 200 |
| Vrsta | 232.30 |