

Datum: 26.04.2026



(slika je simbolična)

## Medprirobnični zaporni ventil, Pneum. vklop, DN 125

Kategorija: [Butterfly valve, with double-acting actuator](#)  
Šifra: **103672RIE**

### Kratek opis

Intermediate flange blocking flap, Pneumat. actuation drive, double-acting, Operating temp. -15°C to 120°C, DN 125, PN max. 16 bar  
Butterfly valves with pneumatic actuator. Pneumatic actuators, double- or single acting version.  
For water/steam, seawater, salt water, ester, ketones, alkalis, caustic soda, sodium hydroxide.  
Not recommended for hydrocarbons, oils or greases.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Adapter ventila	Supplied as standard, operated by a 3/2- or 5/2-way valve
Disc	Stainless steel
Gred izbirnika	CF8M/1.4404
Ohišje	SS416
Pogonski material	Grey cast iron GG25
Premaz za pogon	epoxy resin coated, RAL 5015 color
Različica	Anodised aluminium
Tesnilo	NBR
Tesnilo gredi izbirnika	double-acting
Min. vodeni tlak [bar]	EPDM
Max. vodeni tlak [bar]	EPDM
Max. obratovalni tlak [bar]	5
B [mm]	5.5
Kot vrtenja [°]	16
Max. delovna temperatura [°C]	59.0
H1 [mm]	90
DN	120
L [mm]	123.0
H2 [mm]	125
H3 [mm]	190.0
	191.0
	321.0