

Datum: 26.06.2026



(slika je simbolična)

## Medprirobnični zaporni ventil, Pneum. vklop, DN 65

Kategorija: [Butterfly valve, with double-acting actuator](#)Šifra: **103669RIE**

### Kratek opis

Intermediate flange blocking flap, Pneumat. actuation drive, double-acting, Operating temp. -15°C to 120°C, DN 65, PN max. 16 bar

Butterfly valves with pneumatic actuator. Pneumatic actuators, double- or single acting version.

For water/steam, seawater, salt water, ester, ketones, alkalis, caustic soda, sodium hydroxide.

Not recommended for hydrocarbons, oils or greases.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Adapter ventila	Supplied as standard, operated by a 3/2- or 5/2-way valve
Disc	Stainless steel
Gred izbirnika	CF8M/1.4404
Ohišje	SS416
Pogonski material	Grey cast iron GG25
Premaz za pogon	epoxy resin coated, RAL 5015 color
Različica	Anodised aluminium
Tesnilo	NBR
Tesnilo gredi izbirnika	double-acting
Min. vodeni tlak [bar]	EPDM
Max. vodeni tlak [bar]	EPDM
Max. obratovalni tlak [bar]	5
B [mm]	5.5
DN	16
H1 [mm]	49.0
Kot vrtenja [°]	65
L [mm]	78.0
Max. delovna temperatura [°C]	90
H2 [mm]	115.0
H3 [mm]	120
	155.0
	259.0