

Datum: 14.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

[mehka PVC obrate cev Komp., hit spojkamie Ø 14.5x9, 15m](#)

Kategorija: [Soft PVC workshop hose, quick disconnect coupling](#)
Šifra: **113848RIE**

Kratek opis

Soft PVC workshop hose set, Quick-connect coupling I.D. 7.2, Hose Ø 14.5x9, PN at 20 °C max. 15 bar, Length 15 m
Highly flexible hose for compressed air applications in workshop areas. Assembled with brass stem and brass quick disconnect coupling DN 7.2 optional with pushbutton safety coupling DN 7.4 and galvanised steel stem.
Not suitable for direct attachment to pulsating tools.
We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Pletenica	High-strength polyester fabric
Zračnico	Soft PVC, black
Zunanji pokrov	Soft PVC, blue
I.D. cevi [mm]	9
O.D. cevi [mm]	14.5
Dolžina cevi [m]	15
Max. obratovalni tlak pri 20 °C [bar]	15
Max. delovna temperatura [°C]	60