

Datum: 13.06.2026



(slika je simbolična)

Merilnik diferenčnega tlaka »FUTURA« Vel.2, 200 - 5000 l / min

Kategorija: [Differential pressure flow meter](#)
Šifra: **100330RIE**

Kratek opis

Differential pressure flow meter »FUTURA«, Size 2, Measurement range 200 - 5000 L/min, Operating pressure 0 - 16 bar

Differential pressure measuring system for detecting changes in flow rate or consumption and measuring energy efficiency. There is a differential pressure at the sensor as soon as a fluid starts to flow. Fast and accurate measurements can be achieved in this way. This robust instrument in a modern design offers a high level of safety (codable) and requires no maintenance.

Accessories:

Wall bracket or alternative a mounting bracket for wall mounting as a component of the »FUTURA« service unit.

Wall brackets with a connection thread for mounting to an existing compressed air system.

Joiner set for easy adaptation as a component of the »FUTURA« service unit.

Adapter plates for adapting different »FUTURA« service unit sizes.

Tehnične Specifikacije

Izhodni volumnski pretok	Analog 0 to 10 V
Merilni sistem	Differential pressure method
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Zaslona	Background lighting
Velikost	2
Max. obratovalni tlak [bar]	16
Operativna napetost	24 V DC
Max. temperaturno območje [°C]	50
Min. merilno območje [l/min]	200
Max. merilno območje [l/min]	5000