

Datum: 12.04.2026



## Merilnik pretoka dif. tlaka»FUTURA«Vel. 2, 150-2000 l/min

Kategorija: [Differential pressure flow meter](#)  
Šifra: **100329RIE**

(slika je simbolična)

### Kratek opis

Differential pressure flow meter »FUTURA«, Size 2,  
Measurement range 150 - 2000 L/min, Operating pressure 0  
- 16 bar

Differential pressure measuring system for detecting  
changes in flow rate or consumption and measuring energy  
efficiency. There is a differential pressure at the sensor as  
soon as a fluid starts to flow. Fast and accurate  
measurements can be achieved in this way. This robust  
instrument in a modern design offers a high level of safety  
(codable) and requires no maintenance.

Accessories:

Wall bracket or alternative a mounting bracket for wall  
mounting as a component of the  
»FUTURA« service unit.

Wall brackets with a connection thread for mounting to an  
existing compressed air system.

Joiner set for easy adaptation as a component of the  
»FUTURA« service unit.

Adapter plates for adapting different »FUTURA« service unit  
sizes.

### Tehnične Specifikacije

Izhodni volumski pretok	Analog 0 to 10 V
Merilni sistem	Differential pressure method
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Zaslona	Background lighting
Velikost	2
Max. obratovalni tlak [bar]	16
Operativna napetost	24 V DC
Max. temperaturno območje [°C]	50
Min. merilno območje [l/min]	150
Max. merilno območje [l/min]	2000