

Datum: 25.06.2026



(slika je simbolična)

MikroFilter brez diferenčnega manometra, 0.01 µm, G 1/2

Kategorija: [Microfilter without differential pressure gauge](#)Šifra: **101570RIE**

Kratek opis

Microfilter without differential pressure gauge, 0.01 µm, G 1/2, Input pressure 4 - 12 bar, Medium / ambient temp. 5 °C to 60 °C

Ideal for filtering out aerosols and solid impurities larger than 0.01 µm.

Micro-filters should always be used in conjunction with a pre-filter.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Element filtra | Borosilicate (with glass-fibre material and foam plastic) |
| Merjenje pretoka | At $P_1 = 6$ bar and pressure drop $\Delta_p = 1.5\%$ |
| Navoj | G 1/2 |
| Ohišje | Aluminium |
| Posoda filtra | Aluminium |
| Rang filtra [µm] | 0.01 |
| Min. vhodni tlak [bar] | 4 |
| Min. sobna temperatura [°C] | 5 |
| Min. temperatura medija [°C] | 5 |
| Max. vhodni tlak [bar] | 12 |
| C [mm] | 57.0 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| A [mm] | 83.0 |
| Učinkovitost [%] | 99.9999 |
| B2 [mm] | 335.0 |
| D [mm] | 353.0 |
| Pretok [l/min] | 1300 |