



(slika je simbolična)

MikroFilter »FUTURA-mali«, z PC zbiralnik, Velikost 0, G 1/4

Kategorija: [Microfilter with polycarbonate bowl](#)
Šifra: **142449RIE**

Kratek opis

Microfilter »FUTURA-mini«, PC container, 0.01 μm , Size 0, G 1/4, Input pressure 1.5 - 12 bar, Temp. -10°C to 50°C, Fully-automatic

Micro-filters in modern design for compliance with strict compressed air purity requirements.

Micro-filters are used to separate solid oil, water and solid impurities as small as 0.01 μm from compressed air and gases.

Tehnične Specifikacije

| | |
|--|---|
| Min. temperaturno območje [°C] | -10 |
| Element filtra | Borosilicate glass fibre |
| Ločevanje prahu | > 0.01 μm 99.999 % At $P_2 = 6$ bar and pressure drop $\Delta_p = 0.1$ bar |
| Merjenje pretoka | G 1/4 |
| Navoj | Fully-automatic |
| Odtok kondenzata | PA66 GF60 |
| Ohišje | Polycarbonate container |
| Posoda | Plastic |
| Priključni navoj | FUTURA-mini |
| Serijska | Compressed air, neutral gases |
| Srednje | NBR |
| Tesnilo | |
| Vsebnost olja v ostanku [mg/m ³] | < 0.01 |
| Rang filtra [μm] | 0.01 |
| Min. vhodni tlak [bar] | 1.5 |
| Max. vhodni tlak [bar] | 12 |
| C [mm] | 27.0 |
| A [mm] | 43.0 |
| Max. temperaturno območje [°C] | 50 |
| B [mm] | 170.0 |
| Pretok [l/min] | 190 |