

Datum: 26.06.2026



MikroFilter»FUTURA«PC zbir.0.01 µmVel.4,G 3/4Pol avto.

Kategorija: [Microfilter with polycarbonate bowl and bowl guard](#)
Šifra: **100179RIE**

(slika je simbolična)

Kratek opis

Microfilter »FUTURA«, PC container and protective cage, 0.01 µm, Size 4, G 3/4, 1.5-16 bar, Temp. -10 °C to 50 °C, Semi-automatic
Micro-filters in modern design for compliance with strict compressed air purity requirements.
Micro-filters are used to separate solid oil, water and solid impurities as small as 0.01 µm from compressed air and gases.

Tehnične Specifikacije

| | |
|--|--|
| Min. temperaturno območje [°C] | -10 |
| Element filtra | Borosilicate glass fibre |
| Ločevanje prahu | > 0.01 µm 99.999 % At P ₂ = 6 bar and pressure drop Δ _p = 0.1 bar |
| Merjenje pretoka | G 3/4 |
| Navoj | Semi-automatic |
| Odtok kondenzata | PA66 GF60 |
| Ohišje | Polycarbonate container with protective cage |
| Posoda | Material: Die-cast zinc |
| Priključni navoj | FUTURA |
| Serijska | Compressed air, neutral gases |
| Srednje | |
| Vsebnost olja v ostanku [mg/m ³] | < 0.01 |
| Rang filtra [µm] | 0.01 |
| Min. vhodni tlak [bar] | 1.5 |
| Velikost | 4 |
| Max. vhodni tlak [bar] | 16 |
| Max. temperaturno območje [°C] | 50 |
| C [mm] | 63.0 |
| A [mm] | 85.0 |
| B [mm] | 252.0 |
| Pretok [l/min] | 1500 |