



(slika je simbolična)

## MikroFilter »multifix«PC zbir.Protec. cageVel. 3G 1/2

Kategorija: [Microfilter with polycarbonate bowl and bowl guard](#)  
Šifra: **100536RIE**

### Kratek opis

Microfilter »multifix«, PC container and protective cage, 0.01  $\mu\text{m}$ , Size 3, G 1/2, Input pressure max. 16 bar, Temp. max. 60 °C  
For filtering out solid impurities larger than 0.01  $\mu\text{m}$ .

### Tehnične Specifikacije

|  |   |
|--|---|
| Element filtra                                     | Borosilicate-POM  |
| Merjenje pretoka                                   | At $P_1 = 6$ bar and pressure drop $\Delta_p = 0.1$ bar |
| Navoj  | G 1/2   |
| Odtok kondenzata                                   | Semi-automatic  |
| Ohišje   | Die-cast zinc   |
| Posoda   | Polycarbonate container with protective cage            |
| Serija   | multifix  |
| Tesnilo  | NBR   |
| Rang filtra [ $\mu\text{m}$ ]                      | 0.01  |
| Vsebnost olja v ostanku [ $\text{mg}/\text{m}^3$ ] | 0.01  |
| Velikost   | 3   |
| DN   | 15  |
| Max. vhodni tlak [bar]                             | 16  |
| C [mm]   | 38.5  |
| Max. sobna temperatura [°C]                        | 60  |
| Max. temperatura medija [°C]                       | 60  |
| A [mm]   | 68.8  |
| Učinkovitost [%]                                   | 99.999  |
| D [mm]   | 147.3   |
| B [mm]   | 185.8   |
| Pretok [l/min]                                     | 720   |