



(slika je simbolična)

## MikroFilter »multifix« z PC zbiralnik, 0.01 µm, Velikost 3, G 1/2

Kategorija: [Microfilter with polycarbonate bowl](#)  
Šifra: **100534RIE**

### Kratek opis

Microfilter »multifix« with PC container, 0.01 µm, Size 3, G 1/2, Input pressure max. 16 bar, Medium / ambient temp. max. 60 °C  
For filtering out solid impurities larger than 0.01 µm.

### Tehnične Specifikacije

Element filtra	Borosilicate-POM
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 0.1$ bar
Navoj	G 1/2
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc
Opis	Micro-filters with polycarbonate bowl
Posoda	Polycarbonate container
Serija	multifix
Tesnilo	NBR
Rang filtra [µm]	0.01
Vsebnost olja v ostanku [mg/m <sup>3</sup> ]	0.01
Velikost	3
DN	15
Max. vhodni tlak [bar]	16
C [mm]	38.5
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	68.8
Učinkovitost [%]	99.999
D [mm]	147.3
B [mm]	185.8
Pretok [l/min]	720