

Datum: 01.04.2026



(slika je simbolična)

## MikroFilter »variobloc«Kov. pos.0.01 µmVel.1,G 3/8

Kategorija: [Microfilter with metal bowl, incl. sight glass](#)  
Šifra: **125321RIE**

### Kratek opis

Microfilter »variobloc«, Metal container incl. viewing tube, 0.01 µm, Size 1, G 3/8, Input pressure max. 20 bar, Temp. max. 50 °C  
Borosilicate filter for all applications where compliance with strict compressed air purity requirements is vital.  
As the second stage downstream of the standard filter, the micro-filter removes 99.999 % of even the finest remaining particles from water, oil and dirt with practically zero residues (filter rating: 0.01 µm).

### Tehnične Specifikacije

Kakovost zraka po ISO 8573.1	Class 1 dirt, class 1 oil
Merjenje pretoka	At $P_1 = 7$ bar and pressure drop $\Delta p = 0,1$ bar
Navoj	G 3/8
Posoda	Metal container with viewing tube
Serija	variobloc
Rang filtra [µm]	0.01
Velikost	1
Max. vhodni tlak [bar]	20
C [mm]	22.0
A [mm]	48.0
Max. temperatura medija [°C]	50
Max. sobna temperatura [°C]	80
Učinkovitost [%]	99.999
B [mm]	155.0
Pretok [l/min]	420