



(slika je simbolična)

MikroFilter »variobloc« Zašč. kletka 0.01 µm Vel. 2G 3/4

Kategorija: [Microfilter with polycarbonate bowl and bowl guard](#)
Šifra: **124814RIE**

Kratek opis

Microfilter »variobloc« with PC container and protective cage, 0.01 µm, Size 2, G 3/4, Input pressure max. 16 bar, Temp. max. 50°C

Borosilicate filter for all applications where compliance with strict compressed air purity requirements is vital.

As the second stage downstream of the standard filter, the micro-filter removes 99.999 % of even the finest remaining particles from water, oil and dirt with practically zero residues (filter rating: 0.01 µm).

Tehnične Specifikacije

| | |
|------------------------------|---|
| Kakovost zraka po ISO 8573.1 | Class 1 dirt, class 1 oil |
| Merjenje pretoka | At $P_1 = 7$ bar and pressure drop $\Delta p = 0,1$ bar |
| Navoj | G 3/4 |
| Posoda | Polycarbonate container with protective cage variobloc |
| Serija | |
| Rang filtra [µm] | 0.01 |
| Velikost | 2 |
| Max. vhodni tlak [bar] | 16 |
| C [mm] | 26.0 |
| Max. sobna temperatura [°C] | 50 |
| Max. temperatura medija [°C] | 50 |
| A [mm] | 70.0 |
| Učinkovitost [%] | 99.999 |
| B [mm] | 202.0 |
| Pretok [l/min] | 1100 |