



(slika je simbolična)

## Mini izpu.vent., 1.4305, G 1/8, vkl. prit. 3 - 7 bar

Kategorija: [Stainless steel blow-off safety valve, G 1/8](#)  
Šifra: **103917RIE**

### Kratek opis

Mini bleeder valve, Stainless steel, not component checked,  
Operating temp. -20 °C to 180 °C, G 1/8, Trigger pressure 3  
- 7 bar

Manual adjustment of the blow-off pressure (lock nut).

For compressed air and non-toxic, non-flammable gases,  
cannot be used for liquids due to free blow-off, not suitable  
for steam.

### Tehnične Specifikacije

|                                |                           |
|--------------------------------|---------------------------|
| Min. delovna temperatura [°C]  | -20                       |
| Material                       | Stainless steel<br>1.4305 |
| Navoj                          | G 1/8                     |
| Tesnilo                        | FKM                       |
| Vzmet                          | Stainless steel<br>1.4310 |
| Min. obratovalni tlak [bar]    | 0.5                       |
| Min. nastavljeni tlak [bar]    | 3                         |
| narediti [mm]                  | 3.0                       |
| D [mm]                         | 7.0                       |
| Max. nastavljeni tlak [bar]    | 7                         |
| a/f [mm]                       | 16                        |
| C [mm]                         | 27.0                      |
| Max. obratovalni tlak [bar]    | 60                        |
| Max. delovna temperatura [°C]  | 180                       |
| Hitrost izpiranja max. [l/min] | 350                       |