

Datum: 01.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Mini izpu.vent., 1.4305, G 1/8, vkl. prit. 6 - 12 bar

Kategorija: [Stainless steel blow-off safety valve, G 1/8](#)
Šifra: **103918RIE**

Kratek opis

Mini bleeder valve, Stainless steel, not component checked,
Operating temp. -20 °C to 180 °C, G 1/8, Trigger pressure 6
- 12 bar

Manual adjustment of the blow-off pressure (lock nut).

For compressed air and non-toxic, non-flammable gases,
cannot be used for liquids due to free blow-off, not suitable
for steam.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Material	Stainless steel
	1.4305
Navoj	G 1/8
Tesnilo	FKM
Vzmet	Stainless steel
	1.4310
Min. obratovalni tlak [bar]	0.5
narediti [mm]	3.0
Min. nastavljeni tlak [bar]	6
D [mm]	7.0
Max. nastavljeni tlak [bar]	12
a/f [mm]	16
C [mm]	27.0
Max. obratovalni tlak [bar]	60
Max. delovna temperatura [°C]	180
Hitrost izpiranja max. [l/min]	650