



TN/TS 92GG LR
- Raccordo di estremità diritto
guarnizione gomma
- Male Stud Couplings rubber seal

Filettatura:
Gas cilindrica

Thread:
B.S.P. parallel

Forma E DIN 3852 Foglio 11

Type E DIN 3852 Part 11

Serie Series	Ø Tubo Tube O.D. d ₁	PN	I	L	L1	CH1	Ø F	Ø N	CH2	L2	Completo Complete		Peso - Weight kg.×100 P.	
											Articolo Item	Codice Code	Completo Complete	Solo corpo Only body
L	6	315	8	23	8,5	14	1/8"	14	14	15,5	TN 92 GG - 6 LR	TN092GL06R	2,4	1,5
	6		12	25	10	14	1/4"	19	19	17	TN 92 GG - 6 LR 1/4"	TN092GL06R04	3,9	2,5
	6		12	26	11,5	14	3/8"	22	22	18,5	TN 92 GG - 6 LR 3/8"	TN092GL06R06	5,6	4,6
	8		8	24	8,5	17	1/8"	14	14	15,5	TN 92 GG - 8 LR 1/8"	TN092GL08R02	3,1	1,7
	8		12	25	10	17	1/4"	19	19	17	TN 92 GG - 8 LR	TN092GL08R	4,3	3,1
	8		12	26	11,5	17	3/8"	22	22	18,5	TN 92 GG - 8 LR 3/8"	TN092GL08R06	6,0	4,6
	8		14	27	12	17	1/2"	27	27	19	TN 92 GG - 8 LR 1/2"	TN092GL08R08	8,9	7,6
	10		8	26	11	19	1/8"	14	17	18	TN 92 GG - 10 LR 1/8"	TN092GL10R02	4,2	1,7
	10		12	26	11	19	1/4"	19	19	18	TN 92 GG - 10 LR	TN092GL10R	4,7	2,4
	10		12	27	12,5	19	3/8"	22	22	19,5	TN 92 GG - 10 LR 3/8"	TN092GL10R06	6,4	4,7
	10		14	28	13	19	1/2"	27	27	20	TN 92 GG - 10 LR 1/2"	TN092GL10R08	9,3	6,9
	12		12	26	12	22	1/4"	19	19	19	TN 92 GG - 12 LR 1/4"	TN092GL12R04	5,9	3,4
	12		12	27	12,5	22	3/8"	22	22	19,5	TN 92 GG - 12 LR	TN092GL12R	7,0	3,8
	12		14	28	13	22	1/2"	27	27	20	TN 92 GG - 12 LR 1/2"	TN092GL12R08	9,9	6,8
	15		12	29	13,5	27	3/8"	22	24	20,5	TN 92 GG - 15 LR 3/8"	TN092GL15R06	9,8	5,4
	15		14	29	14	27	1/2"	27	27	21	TN 92 GG - 15 LR	TN092GL15R	11,6	7,2
	15		16	30	15	27	3/4"	32	32	22	TN 92 GG - 15 LR 3/4"	TN092GL15R12	16,5	11,8
	18		14	31	14,5	32	1/2"	27	27	22	TN 92 GG - 18 LR	TN092GL18R	13,8	6,6
	18		16	30	14,5	32	3/4"	32	32	22	TN 92 GG - 18 LR 3/4"	TN092GL18R12	18,2	10,9
	L		22	160	14	33	16,5	36	1/2"	27	32	24	TN 92 GG - 22 LR 1/2"	TN092GL22R08
22		16	33		16,5	36	3/4"	32	32	24	TN 92 GG - 22 LR	TN092GL22R	18,8	9,5
22		18	34		17,5	36	1"	40	41	25	TN 92 GG - 22 LR 1"	TN092GL22R16	28,3	18,3
28		16	34		17,5	41	3/4"	32	41	25	TN 92 GG - 28 LR 3/4"	TN092GL28R12	23,4	16,4
28		18	34		17,5	41	1"	40	41	25	TN 92 GG - 28 LR	TN092GL28R	26,5	15,8
35		18	39		17,5	50	1"	40	46	28	TN 92 GG - 35 LR 1"	TN092GL35R16	38,8	23,3
35		20	39		17,5	50	1" 1/4	50	50	28	TN 92 GG - 35 LR	TN092GL35R	42,4	26,5
42		22	42		19	60	1" 1/2	55	55	30	TN 92 GG - 42 LR	TN092GL42R	58,3	23,0

- Le dimensioni di ingombro si intendono a raccordo chiuso.

- Overall sizes are with closed fitting.

- Per ordinare i raccordi in ACCIAIO INOX (AISI 316) sostituire nel codice di ordinazione la lettera "T" con la lettera "I"

- To order stainless steel fittings (AISI 316), replace the letter "T" with the letter "I"

- Gamma di temperature senza riduzioni di pressione con i raccordi in acciaio con guarnizioni gomma in NBR (di serie) e FPM (su richiesta): NBR (Perbunan): da -35 a +100°C - FPM (Viton): da -25 a +120°C (Per i raccordi in acciaio inox AISI 316 vedere pagine tecniche)

- Temperature range without pressure reductions with steel connections fitted with seals in NBR (standard) and FPM (to order): NBR (Perbunan): from -35 to +100°C - FPM (Viton): from -25 to +120°C (For stainless steel fittings (AISI 316) see technical pages)

- Per ordinare il "solo corpo" sostituire la lettera "N" con la lettera "S"

- To order only body replace the letter "N" with the letter "S"