


Compressed air conditioning





Characteristics

Туре	F 54*	F 55
Port	G 3/4	G 1
Type of construction		
	Centrifugal filter	
	Sintered filter element	
	Special versions on request	
	Special version	ns on request
Input pressure p ₁	Max. 16 bar with plastic bowl	
	Max. 20 bar with m	netal bowl
Input pressure p ₁		
with fully-automatic drain	Max. 16 bar	
(not suitable for	Min. 1.5 bar	
vacuum applications)		
Vacuum		
input pressure p ₁	35 mbar absolute t	o 16 bar
Mounting position	Vertical, drain plug	at bottom
Mounting type	Bracket and two th	rough holes
Medium temperature	Max. 60 °C (other	temperature
Ambient temperature	Max. 60 °C range	es on request)
Filter rating	40 µm	
Bowl capacity	Max. 125 cm ³ conc	lensate
Condensate drain	Semi-automatic	
	Fully-automatic or	n request
Weight [g]	1650	

Materials

Part	Material
Head piece (body)	AI
Adapter	AI
O-ring 81x2	NBR
O-ring 50x2	NBR
Filter element 40 µm	PE
Filter element 8 µm	PE
Air deflector	POM
Baffle	PA
Condensate bowl	Polycarbonate

Ordering information



Port	
5 4	G 3/4
5 5	G 1
Options	
K-HA	Plastic bowl
M-SR	Metal bowl with sight glass
S	Bowl guard

Please use the suffix »A« to order fully-automatic drain (not suitable for vacuum applications)


Order example: F 55 K-HA

Description

- Block design
- _ Simple block mounting with other devices
- using conical clamps and half threads Joiner sets (**KP 55**) are required for block mounting with other devices
- Joiner sets (**KP 55 Z**) are required for block mounting with K 54/55 or T 54/55
- Flow direction: -Entry in direction of arrow
- Filter rating acc. to ISO 4003
- Bowl guard can be retrofitted without tools



Dimensions [mm]



Flow rates


Output pressure $p_2 = [bar]$		6
Nominal flow ($\Delta p = 1 \text{ bar}$)	QN m³/h I/min	480 10500
	1/11111	10200


Accessories

Designation	Order No.
Mounting bracket with 2 screws, cmpl.	ZW 55
Joiner set(s) for block mounting with other devices	KP 55
Joiner set(s) for block mounting with	
K 54/55 or T 54/55	KP 55 Z
Bowl guard	SK 33
Metal bowl with sight glass	MS 33 FS
Metal bowl with sight glass and fully-automatic drain	MS 33 FS-A
Polycarbonate bowl with semi-automatic drain	KS 33 F-HA
Polycarbonate bowl with fully-automatic drain	KS 33 F-A
Filter element 40 µm	655.6.940
Filter element 8 µm	655.6.908
Automatic drain	655.6.900

Main spare parts

Part	Part No.
Filter element 40 µm	655.6.940







Art. No.	Ident No.
F 55 K-HA	100516
F 55 S	100521
F 55 M-SR	100526
ZW 55	100445
KP 55	100446
KP 55 Z	123922
SK 33	100506
MS 33 FS	100502
MS 33 FS-A	100503
KS 33 F-HA	100504
KS 33 F-A	100505
655.6.908	100510
655.6.940	100511
655.6.900	100362

1 -4