

For filtering out solid impurities larger than 0.3 µm.

Max. input pressure:	20 bar
Max. medium temperature:	60 °C
Max. ambient temperature:	60 °C
Drain vale:	Semi-automatic
Sealant:	NBR
Flow rate measurement:	At $P_1 = 6$ bar and pressure drop $\Delta p = 0.02$ bar
Filter rating:	0.3 µm
Efficiency:	99.999 %
Filter element:	Paper-POM

Pre-filter with metal bowl

Art. No.	Type No.	Thread	Housing	Flow rate l/min	Size	DN
133117	FV 44 M	G 3/4	Die-cast aluminium	2000	4	20

Accessories / spare parts

Art. No.	Type No.	Description
135858	ZW 45	Mounting bracket with 2 screws
135857	KP 45	Coupler pack for modular assembly of several devices
135859	KSS 45 F-HA	Polycarbonate bowl, Bowl guard with semi-automatic draining
135860	KSS 45 F-A	Polycarbonate bowl, Bowl guard with fully automatic draining
135861	MS 45 FS	Metal bowl with sight glass and semi-automatic draining
135862	MS 45 FS-A	Metal bowl with sight glass and fully automatic draining
100362	655.6.900	Automatic drain valve
100174	V 864/04	Filter element (paper-aluminium)

