

Housing	Chrome-plated brass
Ball	Nickel-plated brass
Ball seal	PTFE
Stem seal	NBR
Rotating handle	PA 66 glass fibre-reinforced
Operating temperature	-20 to 80 °C
Operating pressure	-0.99 - 20 bar
Thread material	Nickel-plated brass
Standard thread	G-thread acc. to DIN EN ISO 228-1
Applications	Compressed air, water, oil

3-way mini ball valve, L-bore

Art. No.	Type No.	Thread	DN	a/f 1 mm	a/f 2 mm	L mm	G mm	H1 mm	H2 mm
129828	381.01-R	G 1/8 IG	5	17	17	35.0	19.0	33.5	15.5
129829	381.02-R	G 1/4 IG	5	17	17	37.0	19.0	33.5	17.5
129830	381.03-R	G 3/8 IG	7	17	21	42.0	19.0	35.0	19.5

3-way mini ball valve, T-bore

Art. No.	Type No.	Thread	DN	a/f 1 mm	a/f 2 mm	L mm	G mm	H1 mm	H2 mm
129831	382.01-R	G 1/8 IG	5	17	17	35.0	19.0	33.5	15.5
129832	382.02-R	G 1/4 IG	5	17	17	37.0	19.0	33.5	17.5
129833	382.03-R	G 3/8 IG	7	17	21	42.0	19.0	35.0	19.5

