

Cable tie / hose tie from polyamide 6.6 for fast, seamless and reliable bundling of cables, hoses, etc. The black cable tie offers a higher resistance to UV radiation thanks to the enclosed "soot".

Application: electrical installations, industrial cabling, automobile cabling, marine cabling, pre-fab buildings, special applications.

Material Polyamide 6.6  
 Operating temperature -45 °C to 85 °C



### Cable tie, PA 6.6

Art. No.	Type No.	Band width mm	Band length mm	Max. bundle diameter mm	Colour
141427	KB-S-025100	2.5	100	21	black
141428	KB-N-025100	2.5	100	21	natural
141435	KB-S-025190	2.5	200	53	black
141436	KB-N-025190	2.5	200	53	natural
141437	KB-S-036150	3.6	150	36	black
141438	KB-N-036150	3.6	150	36	natural
141439	KB-S-036200	3.6	200	53	black
141440	KB-N-036200	3.6	200	53	natural
141441	KB-S-036300	3.6	300	84	black
141442	KB-N-036300	3.6	300	84	natural
141449	KB-S-048180	4.8	180	43	black
141450	KB-N-048180	4.8	180	43	natural
141451	KB-S-048200	4.8	200	50	black
141452	KB-N-048200	4.8	200	50	natural
141453	KB-S-048250	4.8	250	65	black
141454	KB-N-048250	4.8	250	65	natural
141455	KB-S-048300	4.8	300	81	black
141456	KB-N-048300	4.8	300	81	natural
141457	KB-S-048360	4.8	350	100	black
141458	KB-N-048360	4.8	350	100	natural
141475	KB-S-078450	7.6	450	131	black
141476	KB-N-078450	7.6	450	131	natural
141483	KB-S-088750	9.0	760	230	black
141484	KB-N-088750	9.0	760	230	natural
141487	KB-S-125530	12.0	540	156	black
141488	KB-N-125530	12.0	540	156	natural
141489	KB-S-1251000	12.5	1000	315	black
141490	KB-N-1251000	12.5	1000	315	natural