

Datum: 27.06.2026



## Naoljevalnik»FUTURA«Kov. pos.Kazalno okenceVel.2,G 1/2

Kategorija: [Oil-mist lubricator with metal bowl, sight glass](#)Šifra: **139515RIE**

(slika je simbolična)

### Kratek opis

Mist oiler »FUTURA«, with metal container and viewing tube, Size 2, G 1/2, Input pressure max. 16 bar, Temp. -10 °C to 50 °C

Oil-mist lubricators with excellent flow rates in modern design.

These devices can be used to top up oil automatically.

A hose must be connected to the threaded nipple on the oil bowl for this purpose.

When the oil filling button on the top of the device is pressed, a Venturi nozzle opens and sucks oil into the bowl under vacuum.

### Tehnične Specifikacije

|                                |   |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10   |
| Merjenje pretoka               | At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                          | G 1/2   |
| Ohišje                         | PA66 GF60   |
| Posoda                         | Metal container with viewing tube                     |
| Priključni navoj               | Material: Die-cast zinc                               |
| Razred olja                    | CL 32 acc. to DIN 51517-ISO VG 32                     |
| Serijska                       | FUTURA  |
| Srednje                        | Compressed air, neutral gases                         |
| Tesnilo                        | NBR   |
| Vidna kupola                   | PC  |
| Velikost                       | 2   |
| Max. vhodni tlak [bar]         | 16  |
| Max. temperaturno območje [°C] | 50  |
| A [mm]                         | 63.0  |
| C [mm]                         | 70.0  |
| B [mm]                         | 215.0   |
| Pretok [l/min]                 | 8000  |