

Datum: 27.04.2026

Naoljevalnik»FUTURA«Kov. pos.Kazalno okenceVel.2,G 3/8

Kategorija: [Oil-mist lubricator with metal bowl, sight glass](#)
Šifra: **139514RIE**

(slika je simbolična)

Kratek opis

Mist oiler »FUTURA«, with metal container and viewing tube, Size 2, G 3/8, Input pressure max. 16 bar, Temp. -10 °C to 50 °C

Oil-mist lubricators with excellent flow rates in modern design.

These devices can be used to top up oil automatically.

A hose must be connected to the threaded nipple on the oil bowl for this purpose.

When the oil filling button on the top of the device is pressed, a Venturi nozzle opens and sucks oil into the bowl under vacuum.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Merjenje pretoka	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Ohišje	PA66 GF60
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Razred olja	CL 32 acc. to DIN 51517-ISO VG 32
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Vidna kupola	PC
Velikost	2
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
A [mm]	63.0
C [mm]	70.0
B [mm]	215.0
Pretok [l/min]	8000