



Naoljevalnik»FUTURA«PC zbir.Zašč. kletkaVel.4,G 3/4

Kategorija: [Oil-mist lubricator with polycarbonate bowl](#)
Šifra: **100210RIE**

(slika je simbolična)

Kratek opis

Mist oiler »FUTURA« with PC container and protective cage, Size 4, G 3/4, Input pressure max. 16 bar, Temp. -10 °C to 50 °C

Oil-mist lubricators with excellent flow rates in modern design.

These devices can be used to top up oil automatically.

A hose must be connected to the threaded nipple on the oil bowl for this purpose.

When the oil filling button on the top of the device is pressed, a Venturi nozzle opens and sucks oil into the bowl under vacuum.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Merjenje pretoka	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/4
Ohišje	PA66 GF60
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc CL 32 acc. to DIN 51517-ISO VG 32
Razred olja	FUTURA
Serija	Compressed air, neutral gases
Srednje	NBR
Tesnilo	PC
Vidna kupola	4
Velikost	16
Max. vhodni tlak [bar]	50
Max. temperaturno območje [°C]	85.0
A [mm]	88.0
C [mm]	271.0
B [mm]	14000
Pretok [l/min]	