

Datum: 26.06.2026

## Naoljevalnik »GA« PC zbir.Zašč. kletka, Vel. 300, G 3/8

Kategorija: [Oil-mist lubricator with PC bowl, bowl guard](#)  
Šifra: **178485RIE**

(slika je simbolična)

### Kratek opis

Mist oiler »GA«, PC container, Protective cage, Mounting bracket, Size 300, G3/8, Input pres. max. 10 bar, Working pres. 0.5-9 bar  
Proportional lubricators, oil can be filled under pressure.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-5
Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serija	GA
Tesnilo	NBR
Vidna kupola	Brass/POM
Min. delovni tlak [bar]	0.5
Max. delovni tlak [bar]	9
Max. vhodni tlak [bar]	10
C [mm]	45.0
A [mm]	62.5
Max. temperaturno območje [°C]	70
D [mm]	136.0
B [mm]	181.0
Velikost	300
Pretok [l/min]	5100