



(slika je simbolična)

[Naoljevalnik »multifix-mali« s polikarbonatnim zbiralnikom, G 1/8](#)

Kategorija: [Oil-mist lubricator with polycarbonate bowl](#)
Šifra: **100387RIE**

Kratek opis

Mist oiler »multifix-mini« with polycarbonate container, G 1/8, Input pressure max. 16 bar, Medium / ambient temp. max. 60 °C
Micro-lubricators, oil can be filled under pressure.

Tehnične Specifikacije

| | |
|------------------------------|-------------------------------------------------------|
| Merjenje pretoka | At $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj | G 1/8 |
| Ohišje | Die-cast zinc |
| Posoda | Polycarbonate container |
| Razred olja | CL 32 acc. to DIN 51517-ISO VG 32 |
| Serija | multifix-mini |
| Tesnilo | NBR |
| Vidna kupola | PA |
| DN | 5 |
| Max. vhodni tlak [bar] | 16 |
| A [mm] | 40.0 |
| C [mm] | 49.6 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| D [mm] | 95.5 |
| B [mm] | 145.1 |
| Pretok [l/min] | 1150 |