



(slika je simbolična)

[Naoljevalnik »Stinard« s polikarbonatnim zbir.Vel. 3G 1/2](#)

Kategorija: [Oil-mist lubricator with polycarbonate bowl](#)Šifra: **101017RIE**

Kratek opis

Mist oiler »Standard« with polycarbonate container, Size 3, G 1/2, Input pressure max. 16 bar, Medium / ambient temp. max. 60 °C
Proportional lubricators, oil can be filled under pressure.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1/2 |
| Ohišje | Die-cast zinc, painted silver |
| Posoda | Polycarbonate container |
| Razred olja | CL 32 acc. to DIN 51517-ISO VG 32 |
| Serija | Standard |
| Tesnilo | NBR |
| Vidna kupola | PA |
| Velikost | 3 |
| DN | 15 |
| Max. vhodni tlak [bar] | 16 |
| C [mm] | 55.0 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| A [mm] | 79.0 |
| D [mm] | 157.0 |
| Pretok [l/min] | 4000 |