

Datum: 12.03.2026



Naoljevalnik »variobloc«PC zbir.Protec. cageVel. 2G 3/4

Kategorija: [Oil-mist lubricator with PC bowl and bowl guard](#)
Šifra: **124819RIE**

(slika je simbolična)

Kratek opis

Mist oiler »variobloc«, PC container, protective cage, Size 2, G 3/4, Input pressure max. 16 bar, Medium / ambient temp. max. 50°C

Proportional lubricators, oil can be filled under pressure.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/4
Ohišje	Die-cast zinc
Posoda	Polycarbonate container with protective cage
Razred olja	CL 32 acc. to DIN 51517-ISO VG 32
Serija	variobloc
Tesnilo	NBR
Vidna kupola	PA
Velikost	2
Max. vhodni tlak [bar]	16
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
C [mm]	57.0
A [mm]	70.0
B [mm]	224.0
Pretok [l/min]	7500