



## Naoljevalnik »variobloc« PC zbir. Protec. cage Vel.1, G 3/8

Kategorija: [Oil-mist lubricator with PC bowl and bowl guard](#)  
Šifra: **124817RIE**

(slika je simbolična)

### Kratek opis

Mist oiler »variobloc«, PC container, protective cage, Size 1, G 3/8, Input pressure max. 16 bar, Medium / ambient temp. max. 50°C

Proportional lubricators, oil can be filled under pressure.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

### Tehnične Specifikacije

|                              |   |
|------------------------------|---|
| Merjenje pretoka             | At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 3/8   |
| Ohišje                       | Die-cast zinc   |
| Posoda                       | Polycarbonate container with protective cage          |
| Razred olja                  | CL 32 acc. to DIN 51517-ISO VG 32                     |
| Serija                       | variobloc   |
| Tesnilo                      | NBR   |
| Vidna kupola                 | PA  |
| Velikost                     | 1   |
| Max. vhodni tlak [bar]       | 16  |
| A [mm]                       | 48.0  |
| Max. sobna temperatura [°C]  | 50  |
| Max. temperatura medija [°C] | 50  |
| C [mm]                       | 52.0  |
| B [mm]                       | 171.0   |
| Pretok [l/min]               | 4400  |