

Datum: 20.06.2026



(slika je simbolična)

## Naoljevalnik »variobloc« s kovinsko posodo, Velikost 2, G 1/2

Kategorija: [Oil-mist lubricator, metal bowl, incl. sight glass](#)Šifra: **125337RIE**

### Kratek opis

Mist oiler »variobloc« with metal container incl. viewing tube, Size 2, G 1/2, Input pressure max. 20 bar, Medium temp. max. 80°C

Proportional lubricators, oil can be filled under pressure. Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Ohišje	Die-cast zinc
Posoda	Metal container with viewing tube
Razred olja	CL 32 acc. to DIN 51517-ISO VG 32
Serija	variobloc
Tesnilo	NBR
Vidna kupola	PA
Velikost	2
Max. vhodni tlak [bar]	20
C [mm]	65.0
A [mm]	70.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
B [mm]	224.0
Pretok [l/min]	4600