

Datum: 14.12.2025



(slika je simbolična)

Nast. duš.ventil, za dobavo zraka, pot.i priklop 8,G1/8

Kategorija: [Unidirectional flow control valves](#)
Šifra: **106915RIE**

Kratek opis

Throttle check valve, Supply air throttle (V) push-in connector hose 8, G 1/8, PN max. 10 bar, Temperature -20 °C to 80 °C

For throttling flow rates and regulating the piston speed of cylinders. Small dimensions, ideal for tight spaces. To be screwed directly into the valve or cylinder. The set flow rate can be locked via the lock nut in the version with knurled screw. The variants in banjo bolt construction can be rotated during assembly and are fixed after tightening. The seals and lubricants used are silicone-free.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -20 |
| Design | Banjo bolt construction |
| Ffunkcija | Supply air throttle (V) |
| Navoj | G 1/8 |
| Silicone-free | Yes |
| Telo | Nickel-plated brass |
| Tesnilo | NBR |
| Vrsta povezave | Plug-in connector |
| Zarobljena tesnila | Polyamide, glass fibre-reinforced (only parts in banjo bolt construction) |
| Za cevi [mm] | 8 |
| Max. obratovalni tlak [bar] | 10 |
| a/f [mm] | 14 |
| C [mm] | 23.7 |
| B [mm] | 42.4 |
| Max. temperaturno območje [°C] | 80 |