

Datum: 01.07.2026



(slika je simbolična)

## Natančen Tlačni reg. »multifix«Vel. 3G 1/2, 0.2-6 bar

Kategorija: [Precision pressure regulators](#)Šifra: **100458RIE**

### Kratek opis

Precision pressure regulator »multifix«, incl. pressure gauge, Size 3, G 1/2, Input pressure max. 16 bar, Control range 0.2-6 bar  
Diaphragm pressure regulators, independent of inlet pressure, with self-relieving design and very high flow rate.  
The pressure setting can be locked by pushing the button down.

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Ohišje	Die-cast zinc
Poraba zraka	Yes
Serijska	multifix
Tesnilo	NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.2
Max. notranja poraba zraka	2.6 l/min (depending on secondary pressure)
Velikost	3
Max. krmilno območje [bar]	6
Zaslon manometra max. [bar]	10
DN	15
Max. vhodni tlak [bar]	16
D [mm]	35.1
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	68.8
C [mm]	99.0
B [mm]	134.1
Pretok [l/min]	7600