



(slika je simbolična)

## Natančen Tlačni reg. »multifix«Vel. 3G 1/2, 0.2-6 bar

Kategorija: [Precision pressure regulators](#)  
Šifra: **100458RIE**

### Kratek opis

Precision pressure regulator »multifix«, incl. pressure gauge, Size 3, G 1/2, Input pressure max. 16 bar, Control range 0.2-6 bar  
Diaphragm pressure regulators, independent of inlet pressure, with self-relieving design and very high flow rate.  
The pressure setting can be locked by pushing the button down.

### Tehnične Specifikacije

|                              |   |
|------------------------------|---|
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 1/2   |
| Ohišje                       | Die-cast zinc   |
| Poraba zraka                 | Yes   |
| Serijska                     | multifix  |
| Tesnilo                      | NBR   |
| Vzmet pokrova motorja        | POM-brass   |
| Min. krmilno območje [bar]   | 0.2   |
| Max. notranja poraba zraka   | 2.6 l/min (depending on secondary pressure)                             |
| Velikost                     | 3   |
| Max. krmilno območje [bar]   | 6   |
| Zaslon manometra max. [bar]  | 10  |
| DN                           | 15  |
| Max. vhodni tlak [bar]       | 16  |
| D [mm]                       | 35.1  |
| Max. sobna temperatura [°C]  | 60  |
| Max. temperatura medija [°C] | 60  |
| A [mm]                       | 68.8  |
| C [mm]                       | 99.0  |
| B [mm]                       | 134.1   |
| Pretok [l/min]               | 7600  |