



(slika je simbolična)

Natančen Tlačni reg. »variobloc« Vel. 2, G 3/4, 0.5-10 bar

Kategorija: [Precision pressure regulators](#)
Šifra: **149224RIE**

Kratek opis

Precision pressure regulator »variobloc« incl. pressure gauge, Size 2, G 3/4, Input pressure max. 25 bar, Control range 0.5-10 bar
Pre-pressure independent, reversible diaphragm pressure regulator with secondary venting for applications that require a precise pressure regulation. The line pressure is regulated by the pressure regulator to the set working pressure/secondary pressure and maintains this constantly regardless of pressure fluctuations and air consumption. The precision pressure regulator is characterised by a very low internal air consumption (< 1.5 l/min).

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/4 |
| Ohišje | Die-cast zinc |
| Poraba zraka | Yes |
| Serijska | variobloc |
| Tesnilo | NBR |
| Vzmet pokrova motorja | POM-brass |
| Min. krmilno območje [bar] | 0.5 |
| Max. notranja poraba zraka | 1.5 l/min (depending on secondary pressure) |
| Velikost | 2 |
| Max. krmilno območje [bar] | 10 |
| Zaslon manometra max. [bar] | 10 |
| Max. vhodni tlak [bar] | 25 |
| C [mm] | 33.0 |
| A [mm] | 70.0 |
| Max. sobna temperatura [°C] | 80 |
| Max. temperatura medija [°C] | 80 |
| B [mm] | 134.0 |
| Pretok [l/min] | 8000 |