

Datum: 25.05.2026



(slika je simbolična)

## Natančen Tlačni reg. »variobloc« Vel.1, G 1/4, 0.2-6 bar

Kategorija: [Precision pressure regulators](#)Šifra: **149214RIE**

### Kratek opis

Precision pressure regulator »variobloc«, incl. pressure gauge, Size 1, G 1/4, Input pressure max. 25 bar, Control range 0.2-6 bar

Pre-pressure independent, reversible diaphragm pressure regulator with secondary venting for applications that require a precise pressure regulation. The line pressure is regulated by the pressure regulator to the set working pressure/secondary pressure and maintains this constantly regardless of pressure fluctuations and air consumption. The precision pressure regulator is characterised by a very low internal air consumption (< 1.5 l/min).

### Tehnične Specifikacije

|                              |   |
|------------------------------|---|
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1/4   |
| Ohišje                       | Die-cast zinc   |
| Poraba zraka                 | Yes   |
| Serijska                     | variobloc   |
| Tesnilo                      | NBR   |
| Vzmet pokrova motorja        | POM-brass   |
| Min. krmilno območje [bar]   | 0.2   |
| Velikost                     | 1   |
| Max. notranja poraba zraka   | 1.5 l/min (depending on secondary pressure)                           |
| Max. krmilno območje [bar]   | 6   |
| Zaslon manometra max. [bar]  | 6   |
| Max. vhodni tlak [bar]       | 25  |
| C [mm]                       | 26.0  |
| A [mm]                       | 48.0  |
| Max. sobna temperatura [°C]  | 80  |
| Max. temperatura medija [°C] | 80  |
| B [mm]                       | 98.0  |
| Pretok [l/min]               | 2000  |