

Datum: 16.05.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Nav. koleno 121, 45° Rp 11/4 N.N.R11/4 Z.N. črn.

Kategorija: [Elbow 121, 45°, female/male, black](#)  
Šifra: **133667RIE**

(slika je simbolična)

### Kratek opis

Bracket 121, 45°, Rp 1 1/4 IT, R 1 1/4 ET, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1 According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.  
Working minimal temperature = -20 °C, 25 bar.  
Working pressure for temperature range from -20 °C to 120 °C: 25 bar.  
Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj	Rp/R 1 1/4
Površina	Black
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300