TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 07.11.2026



(slika je simbolična)

Nav. priklj. 330, N.N./N.N.Rp/Rp 1 1/4,č. kovanlit. ž.

Kategorija: Union 330, flat seat, female/female, with NBR-seal
Šifra: **113165RIE**

Kratek opis

Fitting 330, flat sealing, IT/IT, Rp/Rp 1 1/4, NBR seal, Operating temp. -20°C to 200°C, black malleable cast iron, Hot-dip galva.
"
Maximum temperature and maximum operating pressure should not occur at the same time!
Acc. to DIN EN 10242 (formerly DIN 2950)
The classic - and the most popular - screw fitting series for pipe construction.
These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.
They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj	Rp/Rp 1 1/4
Površina	Hot dip galvanised
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	200