

Datum: 26.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Nav. priklj. 330, N.N./N.N.Rp/Rp 1NBR tes.,č. kovanlit. ž.

Kategorija: [Union 330, flat seat, female/female, with NBR-seal](#)  
Šifra: **113164RIE**

### Kratek opis

Fitting 330, flat sealing, IT/IT, Rp/Rp 1, NBR seal, Operating temp. -20°C to 200°C, black malleable cast iron, hot-dip galv.

"  
Maximum temperature and maximum operating pressure should not occur at the same time!  
Acc. to DIN EN 10242 (formerly DIN 2950)  
The classic - and the most popular - screw fitting series for pipe construction.  
These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.  
They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj	Rp/Rp 1
Površina	Hot dip galvanised
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	200