TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 25.11.2026



(slika je simbolična)

Nav. priklj. 330, ravno tesnjenjeN.N./N.N.Rp/Rp 1 1/4

Kategorija: Union 330, flat seat, female/female, black
Šifra: **133810RIE**

Kratek opis

Fitting 330, flat sealing, IT/IT, Rp/Rp 1 1/4, black malleable iron fitting, Operating temp. -20 °C to 200 °C, ISO 7-1
Maximum temperature and maximum operating pressure should not occur at the same time!
According to DIN EN 10242 (previously 2950).
Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj	Rp/Rp 1 1/4
Površina	Black
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	200